

Features

Over-Voltage Protection
Over-Current Protection

Short-circuit Protection
100%Hi-pot & ATE Tested

100%Burn-in under (45°C)

Low Ripple/Noise
MTBF 50000 HRS At 25°C

LVD authentication
Limited Power Sources(LPS)

DoE VI and CoC Tier 2 VI Efficiency
Regulations Compliance

Cispr 22 CLASS B,VCCI CLASS B,
FCC Part15 CLASS B, Compliance

PA1015/PS1015 Series Wall Mount - Britain-Side Plug-In



Specification

Model No		PA1015-xxxxxyyzzz,PS1015-xxxxxyyzzz					
Transformer		EF20	EF20	EF20	EF20	EF20	EF20
Item		5PIN-1	5PIN-2	5PIN-2	5PIN-3	5PIN-4	5PIN-5
Output Voltage		3.0~7.0V	7.1~8.9V	9.0~14.9V	15.0~30.0V	30.1~42.0V	48.0~57.0V
Output Current(Max.)		3.0A	2.14A	1.66A	1.2A	0.5A	0.37A
Output Power(Max.)		15W	15W	15W	18W	18W	24W
Input Voltage		AC90~264V					
Input Frequency		47~63Hz					
Input Current		0.4A Max					
Inrush Current		40A Max					
Line Regulation		1% Max					
Ripple&Noise		1% Max					
Load Regulation		5% Max					
Efficiency		DoE VI & CoC Teir 2 VI					
Operating Temperature		0~40°C					
Storage Temperature		-20~85°C					
Over-Voltage Protection		Auto Recovery					
Short-circuit Protection		Auto Recovery					
Safety Standard		CB UKCA					
EMC(EMI/EMS)		CE UKCA					

機種編碼 Products code:

