

## Features

Over-Voltage Protection  
Over-Current Protection

Short-circuit Protection  
100%Hi-pot & ATE Tested

100%Burn-in under (45°C)

Low Ripple/Noise  
MTBF 50000 HRS At 25°C

LVD authentication  
Limited Power Sources(LPS)

DoE VI and CoC Tier 2 VI Efficiency  
Regulations Compliance

Cispr 22 CLASS B,VCCI CLASS B,  
FCC Part15 CLASS B, Compliance

## PA1015/PS1015 Series Wall Mount/USB - Interchangeable Plug-In



## Specification

Item	Model No	PA1015-xxxxxyyzzz,PS1015-xxxxxyyzzz
	Transformer	EF20 5PIN-1
Output Voltage		5V
Output Current(Max.)		3.0A
Output Power(Max.)		15W
Input Voltage		AC90~264V
Input Frequency		47~63Hz
Input Current		0.4A Max
Inrush Current		40A Max
Line Regulation		1% Max
Ripple&Noise		1% Max
Load Regulation		5% Max
Efficiency		DoE VI & CoC Teir 2 VI
Operating Temperature		0~40°C
Storage Temperature		-20~85°C
Over-Voltage Protection		Auto Recovery
Short-circuit Protection		Auto Recovery
Safety Standard		CB,TUV-GS,CCC,UL,cUL,SAA,RCM,PSE,BSMI,IRAM,KC,KCC,KMEPS,DoE
EMC(EMI/EMS)		CE,FCC,VCCI,RCM

機種編碼 Products code:

