

Features

Over-Voltage Protection
Over-Current Protection

Short-circuit Protection
100%Hi-pot & ATE Tested

100%Burn-in under (45°C)

Low Ripple/Noise
MTBF 50000 HRS At 25°C

LVD authentication
Limited Power Sources(LPS)

DoE VI and CoC Tier 2 VI Efficiency
Regulations Compliance

Cispr 22 CLASS B,VCCI CLASS B,
FCC Part15 CLASS B, Compliance

PA1024/PS1024 Series Wall Mount-USA-Front Plug-In



Specification

Model No	PA1024-xxxxxyyzzz / PS1024-xxxxxyyzzz			
Transformer	EE25-1	EE25-2	EE25-3	EE25-4
Output Voltage	3~7.0V	7.1~15.0V	15.1~30.0V	30.1~57.0V
Output Current(Max.)	4A	4A	1.98A	0.99A
Output Power(Max.)	28W	30W	30W	30W
Input Voltage	AC90~264V			
Input Frequency	47~63Hz			
Input Current	0.6A Max			
Inrush Current	40A Max			
Line Regulation	1% Max			
Ripple&Noise	1% Max			
Load Regulation	5% Max			
Efficiency	DoE VI & CoC Teir 2 VI			
Operating Temperature	0~40°C			
Storage Temperature	-20~85°C			
Over-Voltage Protection	Auto Recovery			
Short-circuit Protection	Auto Recovery			
Safety Standard	CB,UL,cUL,PSE,DoE			
EMC(EMI/EMS)	FCC,VCCI			

機種編碼 Products code:

