

Features

Over-Voltage Protection
Over-Current Protection

Short-circuit Protection
100%Hi-pot & ATE Tested

100%Burn-in under (45°C)

Low Ripple/Noise
MTBF 50000 HRS At 25°C

LVD authentication
Limited Power Sources(LPS)

DoE VI and CoC Tier 2 VI Efficiency
Regulations Compliance

Cispr 22 CLASS B,VCCI CLASS B,
FCC Part15 CLASS B, Compliance

PA1024/PS1024 Series Desk Top -IEC320/C14



Specification

Model No		PA1024-xxxxxyzzz / PS1024-xxxxxyzzz			
Transformer		EE25-1	EE25-2	EE25-3	EE25-4
Item					
Output Voltage		3~7.0V	7.1~15.0V	15.1~30.0V	30.1~57.0V
Output Current(Max.)		4A	4A	1.98A	0.99A
Output Power(Max.)		28W	30W	30W	30W
Input Voltage		AC90~264V			
Input Frequency		47~63Hz			
Input Current		0.6A Max			
Inrush Current		40A Max			
Line Regulation		1% Max			
Ripple&Noise		1% Max			
Load Regulation		5% Max			
Efficiency		DoE VI & CoC Teir 2 VI			
Operating Temperature		0~40°C			
Storage Temperature		-20~85°C			
Over-Voltage Protection		Auto Recovery			
Short-circuit Protection		Auto Recovery			
Safety Standard		CB,CCC,UL,cUL,DoE,TUV-GS,LVD,BSMI,KC,KCC,KMEPS,SAA,RCM,Nrcan,MEPS			
EMC(EMI/EMS)		CE,FCC,VCCI,RCM			

機種編碼 Products code:

