

Features

Over-Voltage Protection
Over-Current Protection

Limit current Protection(Optional)

Short-circuit Protection
100%Hi-pot & ATE Tested

100%Burn-in under (45°C)

Low Ripple/Noise
MTBF 50000 HRS At 25°C

LVD authentication
Limited Power Sources(LPS)

DoE VI and CoC Tier 2 VI Efficiency
Regulations Compliance

Cispr 22 CLASS B, VCCI CLASS B,
FCC Part15 CLASS B, Compliance

PA1040/50/60 Series Desk Top -IEC320/C6



Specification

Model No	PA1040-xyz;PA1050-xyz;PA1060-xyz														
	Transformer	ER28-1 or PQ2620-1		ER28-2 or PQ2620-2		ER28-2 or PQ2620-2		ER28-3 or or PQ2620-2			ER28-4 or PQ2620-3			ER28-5 or PQ2620-4	
Item															
Output Voltage	5.0~8.9V	9~14.9V	9~11.9V	12~14.9V		15~24V			24.1~36V			36.1~57V			
Type(PA1040/50/60)	PA1040	PA1040	PA1050	*50	*60	*40	*50	*60	*40	*50	*60	*40	*50	*60	
Output Current(Max.)	7.0A	4.44A	5A	4.17A	5A	2.66A	3.33A	4A	1.66A	2.07A	2.48A	1.10A	1.38A	1.66A	
Output Power(Max.)	35W	40W	45W	50W	60W	40W	50W	60W	40W	50W	60W	40W	50W	60W	
Input Voltage	AC90~264V														
Input Frequency	47~63Hz														
Input Current	1.5A Max														
Inrush Current	60A Max														
Line Regulation	1% Max														
Ripple&Noise	1% Max														
Load Regulation	5% Max														
Efficiency	DoE VI & CoC Teir 2 VI														
Operating Temperature	0~40°C														
Storage Temperature	-20~85°C														
Over-Voltage Protection	Auto Recovery														
Short-circuit Protection	Auto Recovery														
Safety Standard	CB,UL,cUL,TUV-GS,LVD,MEPS,DoE														
EMC(EMI/EMS)	CE,FCC,VCCI,RCM														

機種編碼 Products code:

