

## Features

Over-Voltage Protection  
Over-Current Protection

Limit current Protection(Optional)

Short-circuit Protection  
100%Hi-pot & ATETested

100%Burn-in under (45°C)

Low Ripple/Noise  
MTBF 50000 HRS At 25°C

LVD authentication  
Limited Power Sources(LPS)

DoE VI and CoC Tier 2 VI Efficiency  
Regulations Compliance

Cispr 22 CLASS B,VCCI CLASS B,  
FCC Part15 CLASS B, Compliance

## PA1045 Series Wall Mount- USA-Side Plug-In



## Specification

Item	Model No		PA1045-XXXXYYZZZ							
	Part No		RM10-1		RM10-2		RM10-3		RM10-4	
Output Voltage	12V~18.9V		19V~24V		24.1V~36V		36V~48V			
Case Type	Wall Mount	Desk Top	Wall Mount	Desk Top	Wall Mount	Desk Top	Wall Mount	Desk Top	Wall Mount	Desk Top
Output Current(Max.)	3.33A	4.0A	2.1A	2.53A	1.66A	2.0A	1.0A	1.33A		
Output Power(Max.)	40W	48W	40W	48W	40W	48W	40W	48W		
Input Voltage	AC90~264V									
Input Frequency	47~63Hz									
Input Current(Max)	1.0A(Wall Mount) & 1.5A(Desk Top)									
Inrush Current	80A Max									
Line Regulation	1% Max									
Ripple&Noise	1% Max									
Load Regulation	5% Max									
Efficiency	DoE VI & CoC Tier 2 VI									
Operating Temperature	0~40°C									
Storage Temperature	-20~85°C									
Over-Voltage Protection	Auto Recovery									
Short-circuit Protection	Auto Recovery									
Safety Standard	CB,UL,cUL,PSE,DoE									
EMC(EMI/EMS)	FCC,VCCI									

