

Features

Over-Voltage Protection
Over-Current Protection

Limit current Protection

Short-circuit Protection
100%Hi-pot & ATE Tested

100%Burn-in under (40°C)

Low Ripple/Noise
MTBF 50000 HRS At 25°C

LVD authentication

DoE VI and CoC Tier VI Efficiency
Regulations Compliance

Cispr 22 CLASS B,VCCI CLASS B,
FCC Part15 CLASS B, Compliance

PS1006 Series

Wall Mount/USB- Interchangeable-Side Plug-In



Specification

Model No	PS1006-xxxxyyyzzz
Transformer	EE16-1
Item	
Output Voltage	5
Output Current(Max.)	1.2A
Output Power(Max.)	6W
Input Voltage	AC90~264V
Input Frequency	47~63Hz
Input Current	0.3A Max
Inrush Current	40A Max
Line Regulation	1% Max
Ripple&Noise	2% Max
Load Regulation	5% Max
Efficiency	DoE VI & CoC Tier 2 VI
Operating Temperature	0~40°C
Storage Temperature	-20~85°C
Over-Voltage Protection	Auto Recovery
Short-circuit Protection	Auto Recovery
Safety Standard	CB,CCC,UL,cUL,TUV-GS,SAA,RCM,KC,KCC,KMEPS,Nrcan,DoE,IRAM
EMC(EMI/EMS)	CE,FCC,VCCI,RCM

