

Features

Over-Voltage Protection
Over-Current Protection

Limit current Protection

Short-circuit Protection
100%Hi-pot & ATE Tested

100%Burn-in under (40°C)

Low Ripple/Noise
MTBF 50000 HRS At 25°C

LVD authentication

DoE VI and CoC Tier VI Efficiency
Regulations Compliance

Cispr 22 CLASS B, VCCI CLASS B,
FCC Part15 CLASS B, Compliance

PS1006 Series Wall Mount- Australia-Side Plug-In



Specification

Item	Model No	PS1006-xxxxxyyzzz		
	Transformer	EE13-1	EE13-1	EE13-2
Output Voltage		5V	7.5V	12V
Output Current(Max.)		1.2A	1.0A	0.6A
Output Power(Max.)		6W	7.5W	7.2W
Input Voltage		AC90~264V		
Input Frequency		47~63Hz		
Input Current		0.3A Max		
Inrush Current		40A Max		
Line Regulation		1% Max		
Ripple&Noise		2% Max		
Load Regulation		5% Max		
Efficiency		DoE VI & CoC Tier 2 VI		
Operating Temperature		0~40°C		
Storage Temperature		-20~85°C		
Over-Voltage Protection		Auto Recovery		
Short-circuit Protection		Auto Recovery		
Safety Standard		CB		
EMC(EMI/EMS)				

機種編碼 Products code:

