

Features

Over-Voltage Protection
Over-Current Protection

Limit current Protection(Optional)

Short-circuit Protection
100%Hi-pot & ATE Tested

100%Burn-in under(45°C)

Low Ripple/Noise
MTBF 50000 HRS At 25°C

LVD authentication
Limited Power Sources(LPS)

DoE VI and CoC Tier 2 VI Efficiency
Regulations Compliance

Cispr 22 CLASS B,VCCI CLASS B,
FCC Part15 CLASS B, Compliance

PS1065 Series Desk Top -IEC320/C14



Specification

Item \ Model No	PS1065-XXXYYYYZZ			
Output Voltage	9~18.9V	19~24V	24.1~36V	36.1~57V
Output Current(Max.)	5A	3.42A	2.7A	1.8A
Output Power(Max.)	65W	65W	65W	65W
Input Voltage	AC90~264V			
Input Frequency	47~63Hz			
Input Current	1.8A Max			
Inrush Current	80A Max			
Line Regulation	1% Max			
Ripple&Noise	1% Max			
Load Regulation	5% Max			
Efficiency	DoE VI & CoC Tier 2 VI			
Operating Temperature	0~40°C			
Storage Temperature	-20~85°C			
Over-Voltage Protection	Auto Recovery			
Short-circuit Protection	Auto Recovery			
Safety Standard	CB,TUV-GS,LVD,cTUVus,BSMI,DoE			
EMC(EM/EMS)	CE,FCC,VCCI,RCM			

