

Features

Over-Voltage Protection
Over-Current Protection

Limit current Protection(Optional)

Short-circuit Protection
100%Hi-pot & ATE Tested

100%Burn-in under(45°C)

Low Ripple/Noise
MTBF 50000 HRS At 25°C

LVD authentication
Limited Power Sources(LPS)

DoE VI and CoC Tier 2 VI Efficiency
Regulations Compliance

Cispr 22 CLASS B,VCCI CLASS B,
FCC Part15 CLASS B, Compliance

PS1065 Series Desk Top-IEC320/C8



Specification

Item	Model No	PS1065-XXXYYYZZZ			
Output Voltage		9~18.9V	19~24V	24.1~36V	36.1~57V
Output Current(Max.)		5A	3.42A	2.7A	1.8A
Output Power(Max.)		65W	65W	65W	65W
Input Voltage		AC90~264V			
Input Frequency		47~63Hz			
Input Current		1.8A Max			
Inrush Current		80A Max			
Line Regulation		1% Max			
Ripple&Noise		1% Max			
Load Regulation		5% Max			
Efficiency		DoE VI & CoC Tier 2 VI			
Operating Temperature		0~40°C			
Storage Temperature		-20~85°C			
Over-Voltage Protection		Auto Recovery			
Short-circuit Protection		Auto Recovery			
Safety Standard		CB,TUV-GS,LVD,cTUVus,CCC			
EMC(EMI/EMS)		CE,FCC,VCCI,RCM			

